



Diluent

Synthetic oil diluent and cleaning liquid



Instructions

Applications: DevoNatural Diluent is a synthetic oil diluent that can be used to dilute DevoNatural High Solid Oil and for manually degreasing wooden, cork and tiled floors, as well as ceilings, furniture, etc. The product is also suitable for cleaning tools, mops, brushes, buckets used to hold the product, etc.

Application:

As a diluent: By diluting 10% DevoNatural High Solid Oil with DevoNatural Diluent, you can prepare a maintenance oil that can be used to thoroughly clean floors, furniture, etc. that have been treated with DevoNatural High Solid Oil.

As a cleaning liquid: Dampen a clean cloth using with DevoNatural Diluent and apply it to the surface that you wish to clean. Remove any excess product using a dry cloth.

Shelf life: Minimum 12 months if kept in properly sealed packaging.

Disposal: Any left-over product should be handled as chemical waste and properly disposed of in compliance with local regulations.

Caution!! Never use undiluted DevoNatural Diluent with electrical devices, due to the risk of explosion.

Diluent

Technical properties

| | |
|---|--|
| Description (type): | Diluent and cleaning liquid |
| Base: | Dearomatised kerosene |
| Characteristic properties: | Volatile |
| Application: | |
| Surface: | Not applicable |
| Material temperature: | Not applicable |
| Air humidity: | Not applicable |
| Material moisture content: | Not applicable |
| Product preparation: | Ready for use |
| Pot life: | Not applicable |
| Application: | |
| Diluent/Cleaning liquid: | |
| Consumption/covering power: | |
| Coat thickness: | Not applicable |
| Finish: | Not applicable |
| Physical and chemical properties: | |
| Colour(s): | Clear |
| Odour: | Characteristic |
| Consistency: | Liquid |
| Dynamic or kinematic viscosity at 20 °C: | 1.14 |
| Specific weight 20 °C/density: | 0.78 – 0.79 kg/l – Method: DIN 53217. |
| Solids by weight: | 0 % |
| VOC content: | 100 % |
| Drying at 20 °C/65% HR: | Not applicable |
| Fully dry after: | Not applicable |
| Gloss (H. 60 °): | Not applicable |
| pH at 20 °C: | Not applicable |
| Water soluble at 20 °C: | Non soluble |
| Vapour pressure/20 °C, mBar: | Not applicable |
| Flash point: | > 21 °C |
| Flammability: | 0.6 – 0.7 % vol |
| Shear strength: | Not applicable |
| Shelf life: | Minimum 12 months if kept in properly sealed packaging |
| Safety: | Contains: Gemisch aliphatischer, naphtenischer Kohlenwasserstoffe; Aromatengehalt: <0,5%. Danger: May be fatal if swallowed and enters airways. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. IF SWALLOWED: Immediately call a POISON CENTER / doctor. Do NOT induce vomiting. Store locked up. Dispose of contents / container in accordance with local / regional / national / international regulations. Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request. |
|  | UN1268 |
| Environmental information: | |
| Bio-degradable: | No |
| Disposal: | Dispose of any left-over product and empty packaging, in compliance with the applicable local regulations. |
| Delivery/Transport: | |
| Available packaging(s): | 1 litre |

© Devomat Industries NV - rév. 2015-07-09a

Please note: This information is based on many years of experience and research. As we are unable to influence the application method, we cannot accept any responsibility on the basis of this information.