

High Solid Oil Renewer

Natural colourless or coloured liquid maintenance oil for renewing or repairing small areas of existing oil layers



Applications: For major maintenance (yearly or every two years) and renewing parquet and wooden floors, furniture, doors, etc. treated with DevoNatural High Solid Oil.
Also suitable for removing localised stains or repairing damage.

- Low consumption: ± 70 m²/litre.
- Easy to apply

Instructions

Surface preparation: The surface must be dry, clean and free of old layers of soap. Always clean first using DevoNatural Intensive Cleaner.

Product preparation: Shake well before use.

Application method:

When renewing a small area (thoroughfare): Apply DevoNatural High Solid Oil Renewer using a dry lint-free cloth and spread across the surface to create a thin and even coat.

When treating an entire room: Coat the floor evenly, using DevoNatural High Solid Oil Renewer, which should be applied using a lint-free cloth or vaporiser (spray) and spread (mop). If desired, the floor can subsequently be polished using a rotating machine fitted with a beige or white pad.

Always remove any excess product, do not apply in layers!

How frequently you will need to apply DevoNatural High Solid Oil Renewer will depend on how much the floor is used.

Drying time: 2 - 4 hours, if well ventilated

Working temperature: 15 - 22 °C

Consumption: 70 m²/litre per treatment

Clean tools: DevoNatural Diluent

Maintenance: DevoNatural Wood Soap. See also the DevoNatural High Solid Oil technical data sheet and DevoNatural maintenance sheet for oiled floors.

Shelf life: Minimum 12 months if kept sealed in packaging

Disposal: Any left-over product should be handled as chemical waste and properly disposed of in compliance with local regulations.

Attention: Before use, please shake the product well and check the colour! The colour effect depends on the type of wood!

In order to prevent spontaneous combustion, soak any cloths and pads used in water or leave to dry in open air! Do not cover the treated floor during the hardening period!

EU value limit for this product (cat A/j): 700 g/l (2010). This produce contains max. 500 g/l VOS.

High Solid Oil Renewer

Technical properties

Description (type):	Maintenance and renewer oil for parquet floors	
Base:	Natural alkyd-based oil, containing linseed oil, tung oil, soya oil, etc.	
Characteristic properties:	Rapid drying and UV resistant	
Application:		
Support:	The surface must be dry, clean and free of old layers of soap.	
Working temperature:	10 – 25 °C.	
Air humidity:	40 – 70 %.	
Material moisture content:		
Product preparation:	Ready for use. Shake well and stir before use.	
Pot life:	Not applicable	
Application:	Use a lint-free cloth, spray or rotating machine	
Diluent/Cleaning liquid:	DevoNatural Diluent	
Consumption/covering power:	70 m ² /litre	
Coat thickness:	Not applicable	
Physical and chemical properties:		
Colour(s):	Colourless, chalk white and vison grey	
Odour:	Natural oils and solvent	
Consistency:	Liquid	
Dynamic or kinematic viscosity at 20 °C:	70 – 90 s	Method: 2 DIN 53211
Specific weight 20 °C/density:	0.90 – 0.95 kg/litre	Method: DIN 53217
Solids by weight:	52 – 60 %	Method: calculation
VOC content:	40 – 48 %	Method: calculation
Drying at 20 °C/65% HR:	Approx. 3 hours	
Fully dry after:	3-5 days	
Gloss (H. 60 °):		
pH at 20 °C:		
Water soluble at 20 °C:	Non	
Vapour pressure/20 °C, mBar:	Not applicable	
Flash point:	> 61 °C	
Spontaneous combustion temperature:	Yes, allow any pads and cloths used to dry in the open air or immerse them in water, in order to prevent spontaneous combustion. Do not cover the floor during the drying period.	
Shear strength:	Not applicable	
Shelf life:	Minimum 12 if kept sealed in packaging	
Safety:	Contains: 2-butanone oxime, Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate. May produce an allergic reaction. Harmful to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid release to the environment. Dispose of contents / container in accordance with local / regional / national / international regulations. Safety data sheet available on request.	
Environmental information:		
Bio-degradable:	No	
Disposal:	Any left-over product should be handled as chemical waste and properly disposed of, in compliance with local regulations.	
Delivery/Transport:		
Available packaging(s):	1 litre	
© Devomat Industries NV - rev. 2018-03-13a	Please note: This information is based on many years of experience and research. As we are unable to influence the application method, we cannot accept any responsibility on the basis of this information.	