

Polish

Water repellent and protective maintenance product for varnished parquet, wood, bamboo and cork floors











Applications: For regular maintenance of varnished parquet, wood, bamboo and cork floors. Restores the floor's original appearance and extends the life of your varnish, if used regularly. Available for matt and satin varnishes.

- The parquet stays attractive for longer
- Increased wear resistance
- Water repellent and stain resistant

Tip: For good lasting results, use the product every 4 - 6 weeks

Instructions

Surface preparation: The surface must be dry, clean and free of grease. The floor must be varnished and should not have been waxed or oiled. Always begin by cleaning the floor using DevoNatural Soft Cleaner. Old layers of polish can be removed using DevoNatural Intensive Cleaner or a rotating machine fitted with a thin purple pad.

Product preparation: Shake well before use. The product can be used undiluted or diluted with water, according to the maximum ratio of 1/10.

Application method: Apply the undiluted product, using a lint-free cloth or diluted in water, using a floor cloth or mop.

<u>Heavily used floors:</u> Apply the undiluted product, using a wax applicator or lint-free cotton cloth. Rub in the direction of the grain of the wood. In order to prevent streaks from appearing, it is advisable to apply several thin coats rather than a single thick coat.

Regular maintenance: Every 4 - 6 weeks, clean with a floor cloth soaked in a mixture of 250 ml DevoNatural Polish diluted in 10 litres of water.

Drying time: After 30 – 90 minutes, depending on the nature of the surface and quantity applied

Dry enough to walk on: After 2 hours

Full curing time: 7 days

Working temperature: 15 - 20 °C, do not apply at temperatures below 12 °C.

Consumption: 70 m²/litre **Clean tools:** Using water

Maintenance: DevoNatural Soft Cleaner and DevoNatural Polish

Shelf life: Minimum 12 months, if protected against frost and kept properly sealed in the packaging.

Disposal: Small quantities may be disposed of with household waste, in compliance with local regulations.

Attention: <u>Do not use on waxed or oiled floors!</u> Coats of varnish must be applied at least 3 weeks before applying DevoNatural Polish.



Polish

Technical properties

Description (type): Protective coating for varnished parquet, wood, bamboo and cork floors

Base: DevoNatural Polish is polyacrylate dispersion-based polish for parquet floors.

Characteristic properties: Water repellent, stain resistant and restores your floor's original appearance

Application:

Surface: The surface must be dry, clean and free of grease. Always start by cleaning the floor with

DevoNatural Soft Cleaner. The floor must be varnished and must not be waxed or oiled.

Material temperature: 10 - 25°C Air humidity: 40 - 70%

Material moisture content:

Product preparation: Shake well before use. The product can be used undiluted or diluted with up to 1/10 water.

Pot life: Not applicabl

Application: Apply the undiluted product, using a lint-free cloth or diluted with water, using a floor cloth or mop.

Diluent/Cleaning liquid: Water

Consumption/covering power: +/- 70 m²/litre
Coat thickness: Not applicable

Physical and chemical properties:

Colour(s): Transparent, whitish Odour: Characteristic Consistency: Liquid

Dynamic or kinematic viscosity at 20 °C: 45-55 s Method: 2 DIN 53211 Specific weight 20 °C/density: 1.01-1.02 kg/l - Method: DIN 53217. Method: DIN 53217 Solids by weight: 12-13 % Method: calculation VOC content: 0-1% Method: calculation

Drying at 20°C/65% RH: +/- 1 hour

Fully dry after:

Gloss (H. 60°): Available as a Matt or Satin Polish. The final appearance depends on the nature of the surface.

pH at 20°C: 8.5 - 9.5

Water soluble at 20 °C:

Vapour pressure/20°C, mBar: Not applicable Flash point: Not applicable

Spontaneous combustion temperature: No

Shear strength: Not applicable

Shelf life: If protected against frost and kept in properly sealed packaging: minimum 12 months

Safety: Keep out of reach of children. If medical advice is needed, have product container or label at hand. Safety

data sheet available on request.

Polish Mat only: Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Environmental information:

Bio-degradable:

Disposal: Small quantities may be disposed of with household waste, in compliance with local regulations.

Delivery/Transport:

Available packaging(s): Matt: 1 litre et 5 litre

Satin: 1 litre et 5 litre

© Devomat Industries SA - rév. 2018-03-13a

Please note: This information is based on many years of experience and research. As we are unable to influence the application method, we cannot accept any responsibility on the basis of this information.